




DC Brushless Water Pump

Bezczotkowa pompa obiegowa FOTTON FT-A38B 24V* DC


Product Parameter								
Model			FOTTON FT-A38B 24V DC					
Character								
Max working voltage			24VDC					
Rated working voltage			12VDC/24VDC (solar Voc max 24V)					
Rated power			18W/28 W					
Hmax Max static water head			3 meters / 5 meters					
Qmax Max static flow rate			6 L/min / 13 L/min					
Lifespan			Continuous operation under normal working surrounding 20000H					
Working Environment			PH value: PH5-10(weak acid and weak base), workable on land, NON submersible.					
Max noise			Under normal working condition,(1meter over the test instrument) 35dB					
Max working temperature			Under room temperature surroundings, fluid medium temperature 90°C (Aluminum body)					
Application			Solar water heater,mobile bath machine, mobile air conditioner, water booster, solar fountain, aquarium, water tank, fish pond, solar water circulation, water circulation of home appliance, crafts, etc.					
Color			Black (Can be customized according to customer`s requirement)					
Outlet direction			Can be adjustable at any angle					
Dimension			IP grade	Inlet		Outlet		Remarks
Length ^ mmV	Width ^ mmV	Height ^ mmV		OD^ mmV	ID^ mmV	OD^ mmV	ID^ mmV	
100.0	47.0	89.0	IP67	G1/2 standard thread	13.0	G1/2 standard thread	13.0	Inlet and outlet have threads.

* uniwersal voltage 12-24V DC for direct connection with PV panels - Voc max 24V

Outside View



Curve Graph



Photo

